



■ ————— **GT-SF-2210-2GC**

PRODUCT OVERVIEW

The GT-SF-2210-2GC provides 8*1000Mbps SFP Slot and 2G SFP+ Slots+ 2*10/100/1000Mbps RJ45 ports, powerful and flexible enough for users to deploy wireless access points or IP-based network surveillance cameras. The switch also comes equipped with 2G SFP+ slots, expanding your network flexibly. In addition, it provides high performance, enterprise-level QoS, advanced security strategies and rich layer 2 management features. With all these advanced features, the Switch is an ideal choice for WIFI coverage, Internet cafes, computer rooms, and so on.

PRODUCT FEATURES

- Panel lights to monitor working state and help fault analysis;
- Flow Control for Full Duplex operation and back pressure for Half Duplex Operation;
- Support Energy-Efficient Ethernet (EEE) function (IEEE802.3az) ;
- Supports a complete lineup of L2 features, including 802.1Q tag VLAN, Port Mirroring, STP/RSTP/MSTP, Link Aggregation Control Protocol and 802.3x Flow Control function;
- Web, CLI (Console Port, Telnet, SSH), SNMP and RMON bring abundant management policies;

PRODUCT SPECIFICATIONS

HARDWARE SPECIFICATION

Model	GT-SF-2210-2GC
Standard	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab , IEEE 802.3z, IEEE 802.3x, IEEE 802.1X, IEEE 802.1q, IEEE 802.1p, IEEE 802.1d , IEEE 802.1w, IEEE 802.3ad
Interface	8*1000Mbps SFP Slots 2G SFP Slots + 2*10/100/1000Mbps RJ45 ports
Indicator	PWR, LNK/ACT, SYS



Network media	10BASE-T: UTP category 3,4,5 cable (≤100m) 100BASE-TX: UTP category 5, 5e cable (≤100m) 1000BASE-T: UTP category 5e, 5 cable (≤100m) 1000BASE-X: MMF, SMF
MAC Address Table	8K, Auto-learning, Auto-aging
jumbo frame	9216Bytes
Transfer Mode	Store-and-forward
Packet Forward Speed	17.85Mpps
Switching Capacity	24Gbps
Dimensions(L*W*H)	280*180*44mm
Fan Quantity	1
Green energy saving	IEEE 802.3az
Surge Protection	Different mode±4KV common mode±6KV
Electrostatic standard	Contact 6KV, air 8KV
Input Power Supply	12V/2A
Operating Temperature	0°C ~ 40 °C

HARDWARE SPECIFICATION

Storage Temperature	-40 °C ~ 70 °C
Operating Humidity	10% ~ 90% non-condensing
Storage Humidity	5% ~ 90% non-condensing
MTBF	>100000 hour

SOFTWARE SPECIFICATION

System	Basic info, System Status, User Management, SNTP , Inport/Export Config, Firmware Upgrade, System reboot/restore factor, System dual image
Network	IPV4/IPV6, DHCP Client/ DHCPV6 Client
Port	Basic config(speed, duplex, flow control), Statistics, Strom Control, Rate Limit, Port-security, Port Mirror, Port Protected, EEE, Jumbo Frame,
Link Aggregation	Load Banlace, LAG, LACP
MAC Address Table	MAC Binding, MAC Learning, MAC Aging, MAC Filter
VLAN	VLAN Basic Config, Voice VLAN, Protocol VLAN, MAC VLAN, Gvrp, Surverillance VLAN
ARP	IP Source Guard, Dynamic ARP Inspection, DoS
DHCP	IP DHCP Snooping, Option82
STP	STP/MSTP/RSTP, Bpdu Guard, Bpdu Filter
SNMP	SNMP Community, SNMP View, SNMP Trap, SNMP(V1,V2C,V3)
RMON	RMON(1,2,3,9)
ACL	MAC ACL/ACE, IPv4 ACL/ACE, IPv6 ACL/ACE
QOS	QOS Queue Scheduling, Cos / Dscp /Ip Precedence Mapping
AAA	Tacacs+, Radius, AAA
IGMP Snooping	IGMP Snooping /Filter, MLD Snooping, MVR
Discovery	LLDP, MED
ONVIF	ONVIF Detect, ONVIF Server
PoE	POE Info, POE Port Config, PD Alive Monitor
Diagnostics	Ping/Ping6, Traceroute, Copper Test, DDMI
Syslog	Logging Management, Debug

SOFTWARE SPECIFICATION

Model	product information
GT-SF-2210-2GC	8G SFP +2G SFP+ 2GE Fiber Managed Switch

Ver : 1.0

NOTE : Specifications are subject to change without notice. Garantir products referred to in this datasheet are trademarks of Garantir or its subsidiaries. All other trademarks belong to their respective owners.