



GT-SG-1216

PRODUCT OVERVIEW

GT-SG-1216 Product have 16*10/100/1000Mbps RJ45 port, Using store and forward technology, combined with dynamic memory allocation, to ensure the effective allocation of bandwidth to each port. This switch is easy to install and does not require configuration, It is easy to manage and maintain which can meet a lot of networking environment, such as Business building, Community, Hotel, Office etc.

PRODUCT FEATURES

- Support IEEE802.3, IEEE802.3u , IEEE802.3z, IEEE802.3x, IEEE802.3az,Standard;
- Flow Control for Full Duplex operation and back pressure for Half Duplex Operation;
- Panel lights to monitor working state and help fault analysis;
- Operation Temperature: 0°C ~ 40 °C;
- Support Energy-Efficient Ethernet (EEE) function (IEEE802.3az) ;
- Line-speed forwarding, intelligent identification;

PRODUCT SPECIFICATIONS

Model	GT-SG-1216
standard	IEEE 802.3、 IEEE 802.3u、 IEEE 802.3z、 IEEE 802.3x、 IEEE802.3az 、 IEEE802.3ab
Port	16 x10/100/1000Mbps RJ45 Port
Forwarding Mode	Storage-and-Forward
Switching Capacity	32Gbps
MAC address table	8K
Jumbo frames	9216K Byte
Packet buffer	4.1M bit
Forwarding Rate	23.8Mpps



Input Power Supply	AC 100-240V 50/60Hz
Operation Temperature	0°C~40°C
Storage Temperature	-40°C~70°C
Operation Humidity	10%~90% RH non-condensing
Storage Humidity	5%~90% RH non-condensing
Dimensions(L*W*H)	280*180*44mm
Fan	Fanless
Weight	<2.5Kg
Green energy saving	IEEE 802.3az
LED Indicator	PWR (Green) , LNK/ACT (Green)
Network Media(Cable)	10BASE-T: UTP category3, 5 cable (≤100m) 100BASE-TX: UTP category5,5e cable (≤100m) 1000BASE-T: UTP category 5e,6 cable(≤100m)
Surge Protection	Different mode±1KV,common mode±2KV
MTBF	>50000 hours
Electrostatic standard	Contact 4KV,air 8KV

ORDERING INFORMATION

Model	product information
GT-SG-1216	16-port Gigabit Switch

Ver : 1.0

NOTE : Specifications are subject to change without notice. Garantir products referred to in this datasheet are trademarks of Garantir or its subsidiaries. All other trademarks belong to their respective owners.