



GARANTIR

## M2M (Male to Male) Audio - Video Cable



Garantir Active High Speed HDMI Cables are the perfect solution for experiencing resolutions up to 4K (4096 x 2160 at 60hz, 4:4:4), bandwidths up to 18.2Gbps.

These cables are designed to exceed the highest measure of HDMI performance and will enhance video experiences with higher resolutions, increased speeds, sharper images and are backward compatible with previous HDMI specifications for existing HDMI devices. They have a built-in signal booster that supports HDMI A/V connections at longer distances up to 100 meters than non-active cables and this cable does not require an external power adapter. Cable also deliver dual video streams, so that two videos can be viewed simultaneously on a single display.

### Feature of Product and Specification

- Supports HDMI 2.0 Version resolutions up to 4K (4096 x 2160 at 60hz, 4:4:4)
- Supports HDMI features including 3D and dual video streams (Dual View)
- Data speeds up to 18.2Gbps
- Supports full HD Blu-ray and HD DVD video
- Premium High-Speed HDMI AOC cable with Ethernet
- Support HDCP 2.2
- Supports HDMI 2.0 Version up to 4K resolutions at 60 Hz
- Fiber optic cable is highly resistant to EMI and RFI interference
- Durable nylon braiding and premium metal connectors
- Gold plated connectors for perfect image quality
- Compatible with all devices that support HDMI
- AOC cable are Thinner and Lighter and more flexible than Conventional HDMI Cable.
- Connectors: 2 x Type-A male, gold plated Corrosion -Resistant
- No external Power require



## Applications

- Videoconference
- Indoor and Outdoor Digital Signage
- Auditorium, Board room
- Switching Application
- In Automation Industries
- ICCC (Integrated Command and Control center)

## Specification

Connectors	HDMI type A Pluggable,
	HDMI type A Pluggable
Fiber optical	Multimode
Data rate	Supports up to 18.2gbps
Compatibility	HDMI 2.0, Support up to 4k @60Hz UHD Content
Power	No External power require
Power Consumption	2.50W max
<b>PHYSICAL DIMENSIONS/ENVIRONMENTAL</b>	
Cable Diameter	4.0mm
Tensile Strength	100N(Long terms ) /200N( Short Terms)
Crush Resistance	200N(Long Terns) 400N (Short Terms)
Bend Radius	80mm/40mm
Operating Temperature	0 to 60 C
Storage Temperature	-30 to 70 C

## ORDERING INFORMATION

<b>GARANTIR AUDIO VIDEO CABLE M2M</b>	
<b>GT- GT-M2M-AV-05</b>	Garantir AUDIO VIDEO CABLE M2M 05M
<b>GT- GT-M2M-AV-10</b>	Garantir AUDIO VIDEO CABLE M2M 10M
<b>GT- GT-M2M-AV-15</b>	Garantir AUDIO VIDEO CABLE M2M 15M



GARANTIR

<b>GT- GT-M2M-AV-35</b>	Garantir AUDIO VIDEO CABLE M2M 35M
<b>GT- GT-M2M-AV-50</b>	Garantir AUDIO VIDEO CABLE M2M 50M
<b>GT- GT-M2M-AV-100</b>	Garantir AUDIO VIDEO CABLE M2M 100M

#### MRP INFORMATION

<b>GARANTIR AUDIO VIDEO CABLE M2M</b>		<b>MRP in INR</b>
<b>GT- GT-M2M-AV-05</b>	Garantir AUDIO VIDEO CABLE M2M 05M	12500
<b>GT- GT-M2M-AV-10</b>	Garantir AUDIO VIDEO CABLE M2M 10M	18000
<b>GT- GT-M2M-AV-15</b>	Garantir AUDIO VIDEO CABLE M2M 15M	25000
<b>GT- GT-M2M-AV-35</b>	Garantir AUDIO VIDEO CABLE M2M 35M	35000
<b>GT- GT-M2M-AV-50</b>	Garantir AUDIO VIDEO CABLE M2M 50M	65000
<b>GT- GT-M2M-AV-100</b>	Garantir AUDIO VIDEO CABLE M2M 100M	85000

Ver : 1.0

NOTE : Specifications are subject to change without notice. Garantir products referred to in this datasheet are trademarks of Garantir or its subsidiaries. All other trademarks belong to their respective owners.